

## The Original



- Complete protection against dust and liquids IP68 (proper installation required)
- Washable, sterilized in just seconds, no seams or crevices
- Resistant against most common disinfectants and detergents
- Low force and precise feedback key technology
- Integrable chassis with sealing lip around (see picture above)
- Low noise typing
- Compact size, ergonomically low profile design
- Damage protected key design
- Integrated high resolution capacitive touchpad
- CleanLock-function to avoid unintended inputs (on option)
- Flexible printing option (laser etching) to realize specific layouts rapidly

Switching technology:	Carbon pills on gold contact
Number of Keys:	105 (incl. 12 function keys)
Protection:	IP68 (NEMA 4X)
Key travel:	1,25 mm
Actuation force:	1 N
Life:	approx. 2 Mio. actuations
Chassis:	OEM (silicone rubber surface)
Interface:	USB
Power:	20mA@5VDC
Dimensions:	358 x 128 x 10 mm (plus 3 mm sealing lip around)
Weight:	0,5 kg
Temperature:	0°C to +60°C
Humidity:	up to 100%
Shock:	3x11 ms pulses (50g) on each of 3 axes
Vibration:	0,04g/Hz, 20Hz-2kHz, 3 hours
Certifications:	CE, FCC Class15, Part B

Part number	Product name	Features
PS00620	K10-MED-OEM-USB-GER	USB, German Layout
PS00621	K10-MED-OEM-USB-US/UK	USB, US-/UK-Layout

Additional versions and modifications are available on request!

Made by ProKeys e.K.  
Karlsbader Straße 1  
08321 Zschorlau  
Phone +49 (0)3771-5644 356  
Fax +49 (0)3771-5644 357  
www.prokeys.de  
info@prokeys.de